

Installer guide and firmware description

FIRMWARE NAME: SSvMIT00; SShMIT00; SScMIT00

CAN TYPE: fault tolerant

PLATFORM: 3901V; 3901T; 330X1

DESCRIPTION:

Data alarm firmware for:

Mitsubishi: Lancer (2007–up); Lancer Evolution (2008–up); Outlander (2006–up); ASX (2010–up)

Peugeot 4007 (2008–up)

Citroen C-Cross (2008–up)

CAN FUNCTIONS:

Function	Available	OBSERVATION
Remote Arm	Yes	Can't arm with any open door
Remote Disarm	Yes	
Panic/Aux Chanel Output	Yes	
Parking Lights	No	
Turn Signals	No	Use analogical output (N1/6) - White
Hood Input	No	Use instant trigger input (N1/4) -Blue
Trunk Release Sensor Bypass	Yes	
Remote Start Sensor Bypass	No	

WIRE COLOR AND LOCATION

Car	Alarm connection		Car connection		
	Function	Wire color	Wire color	Pin	Location
Lancer/ Lancer Evo	Can H	Orange/Green	Yellow	8	Steering Column (see fig.1)
	Can L	Orange/Brown	Lt. Green	9	
	Lights	White	Green	4	Hazard Switch (see fig.2)
Outlander/ 4007/ C-Cross	Can H	Orange/Green	Yellow	8	Steering Column (see fig.1)
	Can L	Orange/Brown	Lt. Green	9	
	Lights	White	Green	4	Hazard Switch (see fig.3)
ASX	Can H	Orange/Green	Green	6	BCM (see fig.4)
	Can L	Orange/Brown	Red	5	
	Lights	White	Light Green	15	BCM (see fig.4)

IMPORTANT:

Factory default settings for **Feature 2-3 (Light Output) - Turn Signal**

Fig.1



Fig.2



Fig.3



Fig.4

