

Installer guide and firmware description

FIRMWARE NAME: SSvCIT01; SShCIT01; SScCIT01

CAN TYPE: Fault tolerant

PLATFORM: 3901V; 3901T; 330X1

DESCRIPTION:

Data alarm firmware for:

CITROEN: **C2**(2005-up); **C3**(2005-up); **C4**(2007-up); **C5**(2005-up); **C6**(2005-up); **DS3**(2010-up);
Jumpy(2006-up);

CAN FUNCTIONS:

Function	Available	OBSERVATION
Remote Arm	Yes	
Remote Disarm	Yes	
Panic/Aux Chanel Output	Yes	
Parking Lights	No	
Turn Signals	Yes	
Hood Input	No	Use instant trigger input (N1/4) – Blue
Trunk Release Sensor Bypass	Yes	
Remote Start Sensor Bypass	No	

WARNING:

After the system is installed on the car, it must be activated with **LEXIA** diagnostic tool.
Please contact an authorized service station.

WIRE COLOR AND LOCATION

Car	Alarm connection		Car connection		
	Function	Wire color	Wire color	Pin	Location
All vehicles	Can H	Orange/Green	-	3	White plug 10 way from BSI. Under driver dashboard
	Can L	Orange/Brown	-	5	

Note: A colour wire is possible to vary with region.

OBSERVATIONS

- Factory default settings for **Feature 2-3 (Light Output) - Turn Signal**
- Car auto-lock action cannot be detected.
- When trunk release button from remote is pressed the system is disarming.